



HP HEATSHIELD MAT

RATED TO: 1100°F CONTINUOUS 2000°F INTERMITTENT

Keep your cool in the heat with our HP Heatshield Mat. When used in applications when there is 1" of airspace and air flow, this heat shield cloth is capable of reflecting 90% of radiant heat. Face the aluminized side toward the source of radiant heat to shield heat away. This product withstands 1100°F of radiant heat (requires minimum of 1" of airspace) and up to 450°F of direct heat. This is perfect for using underneath your floor pan to shield heat from your DPF, muffler, catalytic converter, and exhaust system, or it can be used on your firewall to shield motor heat. It can also be used as a cold air intake heat shield, stick this onto your metal or plastic air box to stop heat from heating up your intake. The HP Heatshield Mat is available with a high temperature peel and stick adhesive. Self-adhesive version is not recommended for rough unfinished fiberglass or carbon fiber. Bulk heat shield cloth rolls available.



PART NO.	DESCRIPTION
720305	36" x 58" no adhesive
720505	58" x 60" no adhesive
721005	18" x 18" w/adhesive (ships folded)
721101	12" x 12" w/adhesive (ships folded)
721102	12" x 24" w/adhesive (ships folded)
721150	12" x 50" w/adhesive
721202	24" x 24" w/adhesive (ships folded)
721204	24" x 48" w/adhesive
721305	36" x 58" w/adhesive
721505	60" x 58" w/adhesive

APPLICATIONS:



FEATURES:

- Continuous operating reflective temperature of 1100°F, 2000°F intermittent
- Capable of reducing up to 90% of radiant heat
- Adhesive backing sticks to almost any clean surface-not recommended for rough/unfinished fiberglass
- Helps shield fire walls, hoods, body panels, floor boards
- All rolls 0.030" thick
- Bulk rolls and custom widths available, minimums apply
- Made in the USA